Product Specifications

CENTURION ELITE®

Operating System

Sensor Capacity

Connectivity

Notification Limit

Outputs

Modular Expansion USBs

Wireless Sensor Frequency

Dimensions Weight

Power Requirement

Battery Back Up

Linux/EOS (Proprietary Elite Operating System)

No Practical Limit

Ethernet (2 Ports), WiFi, Bluetooth®, USB

No Practical Limit

Phone, Email/Text, Two-Way Radio (Customer Provided),

Relays, and Speaker

6

900 MHz

18"Hx13.8"Wx8.4"D

12.5lbs

120V AC

12VDC 7000MA/h



ELITE CONNECT™ WEB PORTAL

Browser Compatibility

Network Connection

Internet Explorer, Google Chrome, Safari, Firefox

WiFi or Ethernet



ELITE CONTROL™ SOFTWARE

Compatible Operating Systems

Software Size

Hardware Requirements

Windows® XP, Windows® 7, Windows® 8, Windows® 10

Operating computer must have a built in,

or add on microphone



PCDURESS®

Network Requirements

Supported Operating Systems

PC Requirements

• Centurion® with a static IP Address

• Centurion® must be accessible from the PC clients via UDP on port 8916

- Less than 15 second network latency preferred
- Applications installed on the client PC must be able to talk via TCP on 8917
- WiFi or Ethernet access to network

Windows® XP, Windows® 7, Windows® 8, Windows® 10, Mac OS® 10.6

Computer must satisfy OS Minimum requirements



PCDuress® Resource Usage 100B every 30 seconds per seat license