























# IP Performance You Want at the Price You Need


Upgrading to IP has never been so easy and affordable. Choose from our full line of quality IP cameras and our intuitive and cost effective Embedded NVRs with a user-friendly configuration process that takes you to live video after only minutes of setup time. Plus it's all backed by Honeywell's unparalleled customer service.











CAT.		PART NUMBER	DESCRIPTION	LENS	IR ILLUMINATION*	RECOMMENDED ACCESSORIES
IR BALL		HEW2PR1	2 MP True Day/Night, WDR, 1 High Power IR LED, Indoor/Outdoor Ball PoE IEEE 802.3af or 12 VDC	3.6 mm Fixed Lens	Smart IR, 130 ft (40 m)	Junction Box: HQA-BB3 Wall Mount: HQA-WK2 Pole Mount: HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		HEW2PRW1	2 MP True Day/Night, WDR, 1 High Power IR LED, Indoor/Outdoor Ball PoE IEEE 802.3af or 12 VDC	3.6 mm Fixed Lens	Smart IR, 130 ft (40 m)	
		HEW4PR3	4 MP True Day/Night, WDR, 1 High Power IR LED, Indoor/Outdoor Ball PoE IEEE 802.3af or 12 VDC	2.8 mm Fixed Lens	Smart IR, 130 ft (40 m)	
		HEW4PRW3	4 MP True Day/Night, WDR, 1 High Power IR LEDs, Indoor/Outdoor Ball PoE IEEE 802.3af or 12 VDC	2.8 mm Fixed Lens	Smart IR, 130 ft (40 m)	
		HEW2PR2	2 MP True Day/Night, WDR, 2 High Power IR LEDs, Indoor/Outdoor Ball PoE IEEE 802.3af or 12 VDC	2.7-12 mm Motorized Focus/Zoom Lens	Smart IR, 200 ft (60 m)	Junction Box: HQA-BB2; HBS2-BB Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		HEW4PR2	4 MP True Day/Night, WDR, 2 High Power IR LEDs, Indoor/Outdoor Ball PoE IEEE 802.3af or 12 VDC	2.7-12 mm Motorized Focus/Zoom Lens	Smart IR, 200 ft (60 m)	
		HED1PR3	1.3 MP True Day/Night, 12 IR LEDs, Indoor/Outdoor Indoor/Outdoor Ball PoE IEEE 802.3af or 12 VDC	2.8 mm Fixed Lens	Smart IR, 100 ft (30 m)	Junction Box: HBS2-BB or HEJB Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		HED3PR3	3 MP True Day/Night, 12 IR LEDs, Indoor/Outdoor Indoor/Outdoor Ball PoE IEEE 802.3af or 12 VDC			
IR RUGGED DOME		H4W2PRV2	2 MP True Day/Night, WDR, 2 High Power IR LEDs, Indoor/Outdoor Mini Dome PoE IEEE 802.3af or 12 VDC	2.7-12 mm Motorized Focus/Zoom Lens	Smart IR, 100 ft (30 m)	Junction Box: HQA-BB2 Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		H4W4PRV2	4 MP True Day/Night, WDR, 2 High Power IR LEDs, Indoor/Outdoor Mini Dome PoE IEEE 802.3af or 12 VDC	2.7-12 mm Motorized Focus/Zoom Lens	Smart IR, 100 ft (30 m)	
		H4W4PRV3	4 MP True Day/Night, WDR, 24 IR LEDs, Indoor/Outdoor Mini Dome PoE IEEE 802.3af or 12 VDC	2.8 mm Fixed Lens	Smart IR, 100 ft (30 m)	
		H2W2PRV3	2 MP True Day/Night, WDR, 10 IR LEDs, Indoor/Outdoor Micro Dome PoE IEEE 802.3af or 12 VDC, built-in mic	2.8 mm Fixed Lens	Smart IR, 65 ft (20 m)	Junction Box: HQA-BB3 Wall Mount: HQA-WK2 Pole Mount: HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		H2W4PRV3	4 MP True Day/Night, WDR, 10 IR LEDs, Indoor/Outdoor Micro Dome PoE IEEE 802.3af or 12 VDC, built-in mic	2.8 mm Fixed Lens	Smart IR, 65 ft (20 m)	
		H4D3PRV3	3 MP True Day/Night, 24 IR LEDs, Rugged Indoor/Outdoor Mini Dome PoE IEEE 802.3af or 12 VDC	2.8 mm Fixed Lens	Smart IR, 100 ft (30 m)	Junction Box: HQA-BB2 Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		H4D3PRV2	3 MP Rugged True Day/Night, 2 High Power IR LEDs, Indoor/Outdoor Mini Dome PoE IEEE 802.3af or 12 VDC	2.7-12 mm Motorized Focus/Zoom Lens	Smart IR, 100 ft (30 m)	Junction Box: HQA-BB2 Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better

\*Depending on scene reflectance

CAT.		PART NUMBER	DESCRIPTION	LENS	IR ILLUMINATION*	RECOMMENDED ACCESSORIES
IR BULLET		<b>HBW2PR1</b>	2 MP True Day/Night, WDR, 2 High Power IR LEDs, Indoor/Outdoor Bullet PoE IEEE 802.3af or 12 VDC	3.6 mm Fixed Lens	Smart IR, 130 ft (40 m)	Junction Box: HQA-BB1 Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		<b>HBW2PR2</b>	2 MP True Day/Night, WDR, 4 High Power IR LEDs, Indoor/Outdoor Bullet PoE IEEE 802.3af or 12 VDC	2.7-12 mm Motorized Focus/Zoom Lens	Smart IR, 200 ft (60 m)	Junction Box: HBS2-BB Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		<b>HBW4PR1</b>	4 MP True Day/Night, WDR, 2 High Power IR LEDs, Indoor/Outdoor Bullet PoE IEEE 802.3af or 12 VDC	3.6 mm Fixed Lens	Smart IR, 130 ft (40 m)	Junction Box: HQA-BB1 Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		<b>HBW4PR2</b>	4 MP True Day/Night, WDR, 4 High Power IR LEDs, Indoor/Outdoor Bullet PoE IEEE 802.3af or 12 VDC	2.7-12 mm Motorized Focus/Zoom Lens	Smart IR, 200 ft (60 m)	Junction Box: HBS2-BB Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		<b>HBD1PR1</b>	1.3 MP True Day/Night, 24 IR LEDs, Indoor/Outdoor Bullet PoE IEEE 802.3af or 12 VDC	3.6 mm Fixed Lens	Smart IR, 100 ft (30 m)	Junction Box: HBS2-BB or HEJB Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better
		<b>HBD3PR1</b>	3 MP True Day/Night, 24 IR LEDs, Indoor/Outdoor Bullet PoE IEEE 802.3af or 12 VDC			
		<b>HBD3PR2</b>	3 MP True Day/Night, 24 IR LEDs, Indoor/Outdoor Bullet PoE IEEE 802.3af or 12 VDC	2.7-12 mm Motorized Focus/Zoom Lens	Smart IR, 100 ft (30 m)	Junction Box: HBS2-BB Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: Cat5e or better

\*Depending on scene reflectance



CAT.		PART NUMBER	DESCRIPTION	RECORDING RATE	REMOVABLE MEDIA
4 CHANNEL		<b>HEN04112</b>	H.264 4 Channel, 4 PoE 1 TB Embedded NVR	120 fps @1080p	2 USB ports (Rear USB 3.0, Front USB 2.0)
		<b>HEN04122</b>	H.264 4 Channel, 4 PoE 2 TB Embedded NVR		
8 CHANNEL		<b>HEN08112</b>	H.264 8 Channel, 8 PoE 1 TB Embedded NVR	240 fps @1080p	
		<b>HEN08122</b>	H.264 8 Channel, 8 PoE 2 TB Embedded NVR		
		<b>HEN08142</b>	H.264 8 Channel, 8 PoE 4 TB Embedded NVR		
16 CHANNEL		<b>HEN16122</b>	H.264 16 Channel, 16 PoE 2 TB Embedded NVR	480 fps @1080p	
		<b>HEN16142</b>	H.264 16 Channel, 16 PoE 4 TB Embedded NVR		
		<b>HEN16162</b>	H.264 16 Channel, 16 PoE 6 TB Embedded NVR		

CAT.		PART NUMBER	DESCRIPTION	COMPATIBLE CAMERAS
MOUNTS		HQA-BB1	Junction Box, Off-White	HBW2PR1, HBW4PR1
		HQA-BB2	Junction Box, Off-White	H4D3PRV2, H4D2PRV3, H4W4PRV3, H4W2PRV2, H4W4PRV2, HEW2PR2, HEW4PR2
		HQA-BB3	Junction Box, Off-White	H2W2PRV3, H2W4PRV3, HEW2PR1, HEW2PRW1, HEW4PR3, HEW4PRW3,
		HBS2-BB	Junction Box, Off-White	HED1PR3, HED3PR3, HBD1PR1, HBD3PR1, HDB3PR2, HBW2PR2, HBW4PR2, HEW2PR2, HEW4PR2
		HEJB	Junction Box, Off-White	HED1PR3, HED3PR3, HBD1PR1, HBD3PR1
		HQA-PM	Pole Mount Adapter, Off-White*	H4D3PRV2, H4D3PRV3, H4W2PRV2, H4W4PRV2, H4W4PRV3, HBD1PR1, HBD3PR1, HBD3PR2, HBW2PR1, HBW4PR1, HBW2PR2, HED1PR3, HED3PR3, HEW2PR2, HEW4PR2
		HQA-PM2	Pole Mount Adapter, Off-White*	H2W2PRV3, H2W4PRV3, H4D3PRV2, H4D3PRV3, H4W2PRV2, H4W4PRV2, H4W4PRV3, HBD1PR1, HBD3PR1, HBD3PR2, HBW2PR1, HBW4PR1, HBW2PR2, HBW4PR2, HED1PR3, HED3PR3, HEW2PR1, HEW2PRW1, HEW2PR2, HEW4PR2, HEW4PR3, HEW4PRW3
		HB34S2-CM	Corner Mount Adapter, Off-White*	H4D3PRV2, H4D3PRV3, H4W2PRV2, H4W4PRV2, H4W4PRV3, HBD1PR1, HBD3PR1, HBD3PR2, HBW2PR1, HBW4PR1, HBW2PR2, HBW4PR2, HED1PR3, HED3PR3, HEW2PR1, HEW2PRW1, HEW2PR2, HEW4PR2
		HQA-WK	Wall Mount, Off-White	HED1PR3, HED3PR3, H4D3PRV2, H4D3PRV3, HEW2PR2, HEW4PR2, H4W4PRV3, H4W2PRV2, H4W4PRV2
		HQA-WK2	Wall Mount, Off-White	H2W2PRV3, H2W4PRV3, HEW2PR1, HEW2PRW1, HEW4PR3, HEW4PRW3

\* With a compatible junction box (please refer to the Mount data sheet at [www.honeywellvideo.com](http://www.honeywellvideo.com))

## Performance Series IP Embedded NVR Kits

Honeywell's Performance Series IP Kits come with your choice of a 1 or 2 TB\* Embedded NVR and four 3 MP IP ball or bullet cameras.













CAT.		PART NUMBER	DESCRIPTION	RECORDING RATE	REMOVABLE MEDIA
4 CHANNEL		HEN04112EB	H.264 4 Channel, 4 PoE 1 TB Embedded NVR with 4 X 3MP Ball Cameras	120 fps@1080p	2 USB ports (Rear USB 3.0, Front USB 2.0)
		HEN04122EB	H.264 4 Channel, 4 PoE 2 TB Embedded NVR with 4 X 3MP Ball Cameras		
		HEN04112BB	H.264 4 Channel, 4 PoE 1 TB Embedded NVR with 4 X 3MP Bullet Cameras		
		HEN04122BB	H.264 4 Channel, 4 PoE 2 TB Embedded NVR with 4 X 3MP Bullet Cameras		

\*Expandable up to 12 TB total (2 HD Bays, 6 TB each)

# Performance Series High Quality Analog (HQA)





## Hassle-Free HD Cameras











Honeywell's Performance Series HQA offers competitively priced cameras for everyday security applications from a partner you know and trust. Performance you want at the price you need.

PERFORMANCE SERIES HQA CAMERAS										
CAT.	PART NUMBER	DESCRIPTION	LENS	RESOLUTION	INPUT VOLTAGE	MINIMUM ILLUMINATION	IR ILLUMINATION*	IP RATING	RECOMMENDED ACCESSORIES	
IR BALL		<b>HD29HD1</b>	Indoor IR Ball, True Day/Night	3.6 mm Fixed Lens	1280 x 720	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 65 ft (20 m)	N/A	Power Supply: HPT12DC500 Junction Box: HBS2-BB Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HD30HD1</b>	Indoor/Outdoor IR Ball, True Day/Night	3.6 mm Fixed Lens	1280 x 720	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 100 ft (30 m)	IP66	Power Supply: HPT12DC500 Junction Box: HQA-BB1 Wall Mount: HQA-WK2 Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HD30HD2</b>	Indoor/Outdoor IR Ball, True Day/Night	3.6 mm Fixed Lens	1928 x 1088	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 100 ft (30 m)	IP66	Power Supply: HPT12DC500 Junction Box: HQA-BB1 Wall Mount: HQA-WK2 Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HD31HD2</b>	Indoor/Outdoor IR Ball, True Day/Night	2.7-12 mm MFZ Lens	1928 x 1088	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 200 ft (60 m)	IP66	Power Supply: HPT12DC500 Junction Box: HBS2-BB; HEJB; HQA-BB2 Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HD231HD2</b>	Indoor/Outdoor IR Ball, True Day/Night, True WDR	2.7-12 mm MFZ Lens	1928 x 1088	12 VDC / 24 VAC	0.0 lux (IR LEDs On)	Smart IR, 200 ft (60 m)	IP66	Power Supply: HPT12DC500 Junction Box: HQA-BB2, HEJB, HBS2-BB Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HD30HD4</b>	4 MP HQA Indoor/Outdoor IR Ball, True Day/Night	3.6 mm Fixed Lens	2560 x 1440	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 164 ft (50 m)	IP66	Wall Mount: HQA-WK2 Junction Box: HQA-BB3 Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34W2-CM
IR RUGGED DOME		<b>HD73HD1</b>	Indoor/Outdoor IR Mini Dome, True Day/Night	2.7-12 mm VF Lens	1280 x 720	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 100 ft (30 m)	IP66, IK10	Power Supply: HPT12DC500 Junction Box: HQA-BB2 Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HD74HD2</b>	Indoor/Outdoor IR Mini Dome, True Day/Night	2.7-12 mm MFZ Lens	1928 x 1088	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 100 ft (30 m)	IP66, IK10	Power Supply: HPT12DC1000 Junction Box: HQA-BB2 Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HD274HD2</b>	Indoor/Outdoor IR Mini Dome, True Day/Night, True WDR	2.7-12 mm MFZ Lens	1928 x 1088	12 VDC / 24 VAC	0.0 lux (IR LEDs On)	Smart IR, 200 ft (60 m)	IP66, IK10	Power Supply: HPT12DC500 Junction Box: HQA-BB2 Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HD72HD4</b>	Rugged 4 MP HQA IR Dome, True Day/Night, True WDR	2.8 mm Fixed Lens	2560 x 1440	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 100 ft (30 m)	IP66, IK10	Wall Mount: HQA-WK2 Junction Box: HQA-BB2 Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM
		<b>HD274HD4</b>	Rugged 4 MP HQA IR Dome, True Day/Night, True WDR	2.7-12 mm VF Lens	2560 x 1440	12 VDC / 24 VAC	0.0 lux (IR LEDs On)	Smart IR, 100 ft (30 m)	IP66, IK10	Wall Mount: HQA-WK2 Junction Box: HQA-BB2 Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM
IR BULLET		<b>HB74HD1</b>	Indoor/Outdoor IR Bullet, True Day/Night	3.6 mm Fixed Lens	1280 x 720	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 100 ft (30 m)	IP66	Power Supply: HPT12DC500 Junction Box: HBS2-BB; HEJB (HD74HD1 only) Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HB75HD1</b>	Indoor/Outdoor IR Bullet, True Day/Night	2.7-12 mm VF Lens	1280 x 720	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 100 ft (30 m)	IP66	Power Supply: HPT12DC500 Junction Box: HQA-BB1 Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HB74HD2</b>	Indoor/Outdoor IR Bullet, True Day/Night	3.6 mm Fixed Lens	1928 x 1088	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 131 ft (40 m)	IP66	Power Supply: HPT12DC500 Junction Box: HQA-BB1 Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
		<b>HB76HD2</b>	Indoor/Outdoor IR Bullet, True Day/Night	2.7-12 mm MFZ Lens	1928 x 1088	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 200 ft (60 m)	IP66	Power Supply: HPT12DC1000 Junction Box: HBS2-BB Wall Mount: HQA-WK Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair

\*Depending on scene reflectance

**PERFORMANCE SERIES HQA CAMERAS**

CAT.	PART NUMBER	DESCRIPTION	LENS	RESOLUTION	INPUT VOLTAGE	MINIMUM ILLUMINATION	IR ILLUMINATION*	IP RATING	RECOMMENDED ACCESSORIES
IR BULLET (CONTINUED)	 <b>HB276HD2</b>	Indoor/Outdoor IR Bullet, True Day Night, True WDR	2.7-12 mm MFZ Lens	1928 x 1088	12 VDC / 24 VAC	0.0 lux (IR LEDs On)	Smart IR, 200 ft (60 m)	IP66	Power Supply: HPT12DC500, Junction Box: HBS2-BB Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM Cable: RG59/RG6 with power pair
	 <b>HB74HD4</b>	4 MP Indoor/Outdoor IR Bullet, True Day/Night, WDR	3.6 mm Fixed Lens	2560 x 1440	12 VDC	0.0 lux (IR LEDs On)	Smart IR, 131 ft (40 m)	IP66	Junction Box: HQA-BB1 Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM
	 <b>HB276HD4</b>	4 MP Indoor/Outdoor IR Bullet, True Day/Night, WDR	2.7-12 mm VF Lens	2560 x 1440	12 VDC / 24 VAC	0.0 lux (IR LEDs On)	Smart IR, 200 ft (60 m)	IP66	Junction Box: HBS2-BB Pole Mount: HQA-PM; HQA-PM2 Corner Mount: HB34S2-CM
PTZ	 <b>HDP302DQI</b>	1080p 30x IR PTZ Dome (Wall Mount Bracket Included)	4.5-135 mm Lens, 30x Optical Zoom	1920 x 1080	24 VAC	0.0 lux (IR LEDs On)	492 ft (150 m)	IP66	Junction Box: HDZJB Pole Mount: HDZPMA Corner Mount: HDZCMA Ceiling Mount: HDZCM1 Cable: RG59/RG6 with power pair

CAT.	PART NUMBER	DESCRIPTION	COMPATIBLE CAMERAS
MOUNTS	 <b>HQA-WK</b>	Wall Mount, Off-White	HD29HD1, HD31HD2, HD231HD2, HD73HD1, HD74HD2, HD274HD2
	 <b>HQA-WK2</b>	Wall Mount, Off-White	HD30HD1, HD30HD2, HD30HD4, HD72HD4, HD274HD4
	 <b>HQA-BB1</b>	Junction Box, Off-White	HD30HD1, HD30HD2, HB74HD2, HB74HD4
	 <b>HQA-BB2</b>	Junction Box, Off-White	HD72HD4, HD274HD4
	 <b>HQA-BB3</b>	Junction Box, Off-White	HD30HD4
	 <b>HEJB</b>	Junction Box, Off-White	HD31HD2, HD231HD2, HB74HD1
	 <b>HBS2-BB</b>	Junction Box, Off-White	HD29HD1, HD31HD2, HD231HD2, HB74HD1, HB75HD1, HB76HD2, HB276HD2, HB276HD4
	 <b>HQA-PM</b>	Pole Mount, Off-White	All Performance Series HQA cameras (with a compatible junction box)
	 <b>HQA-PM2</b>	Pole Mount, Off-White	All cameras except HDP302DQI
	 <b>HB34S2-CM</b>	Corner Mount, Off-White	All Performance Series HQA cameras (with a compatible junction box)

## DVRs

Our digital video recorders support a wide variety of user-friendly capabilities such as mouse operation, IR remote control, remote connectivity and best-in-class search engines.

PERFORMANCE SERIES HQA DVRs			
CAT.	PART NUMBER	DESCRIPTION	STORAGE
4 CH	HRHT4041	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 1HDD-bay High/Standard Definition Analog Hybrid	1 TB
	HRHT4042	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 1HDD-bay High/Standard Definition Analog Hybrid	2 TB
8 CH	HRHT4082	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	2 TB
	HRHT4084	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	4 TB
16 CH	HRHT4162	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	2 TB
	HRHT4164	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	4 TB
	HRHT4166	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	6 TB
	HRHT41612	4 MP 15fps/ch (1080p 25/30 fps/ch) DVR 2HDD-bay High/Standard Definition Analog Hybrid	12 TB



365 SWAP PROGRAM



## FEATURES

\*5-year warranty excludes recorders and PTZ cameras

### Honeywell Security and Fire

2700 Blankenbaker Pkwy, Suite 150

Louisville, KY 40299

1.800.323.4576

www.honeywell.com

L/PSQRG/D | 04/17

© 2017 Honeywell International Inc.